



SYNLawn Roofdeck Premium

Ideal turf for the most demanding applications, including rooftop decks, lounge areas, and gardens. ASTM E108 Class A Fire-Rating ensures projects using this turf will meet safety codes and look great for years to come.

Grass Zone Yarn/Color	PE / Field Green / Olive / Apple
Grass Zone Denier	9,900 / 9
Thatch Zone Yarn/Color	PE / Field Green / Beige
Thatch Zone Denier	5,040 / 12
Grass Zone Yarn Shape	Soft Omega
Finished Pile Height	1 5/8"
Finished Pile Weight	100 oz.
Backing	15 / 18 PP 2-Part / 20oz. EnviroLoc™
Tuft Gauge	3/8"
Total Weight	126 oz.
Tuft Bind	> 8 lbs.
Permeability	> 700 inches per / SY
Features	EnviroLoc™, Deluster, UV Stabilizers
Test Data	ASTM E108 Class A Fire Rating, F1292, F1951

- Unmatched Lifetime Warranty
- EnviroLoc™ Plant-Based Backing
- Deluster and UV Protection
- Class A Fire Rating

Foot Traffic

Softness



RECOMMENDED USES

- ROOFTOP
- LANDSCAPE
- PLAY
- PETS

Primary Yarn Polymer	Polyethylene	Primary Backing	15/18 PP 2-Part
Yarn Cross Section	Soft Omega	Coating Type	20 oz. EnviroLoc™
Standard Color	Field Green / Olive / Apple	PE Yarn Denier / Ends	9,900 / 9
Fabric Construction	Tufted	Texturized Thatch Denier / Ends	5,040 / 12
Second Yarn Polymer Thatch	Polyethylene	Warranty Period	Limited Lifetime
Secondary Yarn Color	Field Green / Beige		

Finish Fabric	English System		ASTM Test
	<i>Nominal Specification</i>	<i>Value</i>	<i>Units</i>
Pile Height (Nominal)	1 5/8	inches	D-5823
Face Weight	100	oz/yd ²	D-5848
Total Fabric Weight	126	oz/yd ²	D-5848
Primary Backing Weight	6	oz/yd ²	D-5848
Secondary Coating Weight	20	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	14,940	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	774.69	in/hr	D-1551
Fabric Width	15	ft	-