





SYNRange PRO

Ideal turf product for large indoor or outdoor applications such as golf facilities and driving ranges. Highly durable with a low face weight and a natural aesthetic are among the many benefits when choosing this golf grass variety.

| | |
|------------------------|--------------------------------------|
| SKU | RANGE |
| Grass Zone Yarn/Color | PE / Field Green / Lime / White |
| Grass Zone Denier | 10,000 / 1 |
| Thatch Zone Yarn/Color | - |
| Thatch Zone Denier | - |
| Grass Zone Yarn Shape | Slit Film |
| Finished Pile Height | 1" |
| Finished Pile Weight | 33 oz. |
| Backing | 15 / 18 PP 2-Part / 22oz. EnviroLoc™ |
| Tuft Gauge | 3/8" |
| Total Weight | 61 oz. |
| Tuft Bind | > 8 lbs. |
| Permeability | > 100 inches per / SY |
| Features | Deluster UV Stabilizers |
| Test Data | - |

-  10 Year Warranty
-  UV Protection
-  Deluster



3 Colors available
Field Green | Lime | White
Ask about Custom Colors



ASK FOR A...



**Dave Pelz
SHOTSTOPPER™
Installation System**



**GreensMaster™
CERTIFIED
Installer**



Dave Pelz

RECOMMENDED USES



GOLF

| | | | |
|----------------------------|--------------------|---------------------------------|-------------------|
| Primary Yarn Polymer | Polyethylene | Primary Backing | 15/18 PP 2-Part |
| Yarn Cross Section | Slit Film | Coating Type | 22 oz. EnviroLoc™ |
| Standard Color | 3 colors available | PE Yarn Denier / Ends | 10,000 / 1 |
| Fabric Construction | Tufted | Texturized Thatch Denier / Ends | - |
| Second Yarn Polymer Thatch | - | Warranty Period | 10 Years |
| Secondary Yarn Color | - | | |

| Finish Fabric | English System | | ASTM Test |
|------------------------------|-----------------------|--------------------|-----------|
| | Nominal Specification | Value | Units |
| Pile Height (Nominal) | 1 | inches | D-5823 |
| Face Weight | 33 | oz/yd ² | D-5848 |
| Total Fabric Weight | 61 | oz/yd ² | D-5848 |
| Primary Backing Weight | 6 | oz/yd ² | D-5848 |
| Secondary Coating Weight | 22 | oz/yd ² | D-5848 |
| Tuft Bind | > 8 | lbs. | D-1335 |
| Grab Tear Strength (Average) | > 200 | lbs. | D-5034 |
| Total Yarn Linear Density | 10,000 | Denier | D-1577 |
| Elongation to Break | > 30 | % | D-2256 |
| Yarn Breaking Strength | > 20 | lbs. | D-5793 |
| Machine Gauge | 3/8 | inches | D-5793 |
| Flammability | Passed | - | D-2859 |
| Water Permeability | > 100 | in/hr | D-1551 |
| Fabric Width | 15 | ft | - |