



SYNFLFESCUE 50

Dazzling realism and luxurious elegance combine to create one of our most popular turf styles — an excellent choice for lawn and landscaping applications.


SKU	FES50
Grass Zone Yarn/Color	PE / Field Green / Apple
Grass Zone Denier	10,800 / 6
Thatch Zone Yarn/Color	PE / Field Green / Beige
Thatch Zone Denier	5,000 / 8
Grass Zone Yarn Shape	S + Omega
Finished Pile Height	1 1/2"
Finished Pile Weight	50 oz.
Backing	13PP/18PET 2pt / 22oz. EnviroLoc+™
Tuft Gauge	3/8"
Total Weight	78 oz.
Tuft Bind	> 8 lbs.
Permeability	> 400 inches p/hr
Features	EnviroLoc+™ HeatBlock™ Deluster, UV Stabilizers
Test Data	-

- UNMATCHED LIFETIME WARRANTY
- OPTIMAL DRAINAGE > 400" PER HOUR
- HEATBLOCK™ TECHNOLOGY
- IDEAL FOR NATURAL LAWN AESTHETICS

INSTALLATION DETAILS AVAILABLE AT



MasterSpec®



NOT TO SCALE. FOR ILLUSTRATION ONLY. CONTACT YOUR LOCAL SYNLAWN FOR INSTALLATION.



Primary Yarn Polymer	Polyethylene	Primary Backing	13PP/18PET 2pt
Yarn Cross Section	S + Omega	Coating Type	22 oz. EnviroLoc+
Standard Color	Field Green / Apple	PE Yarn Denier / Ends	10,800 / 6
Fabric Construction	Tufted	Texturized Thatch Denier / Ends	5,000 / 8
Second Yarn Polymer Thatch	Polyethylene	Warranty Period	Limited Lifetime
Secondary Yarn Color	Beige / Brown		

FINISH FABRIC	ENGLISH SYSTEM		ASTM TEST
	Nominal Specification	Value	Units
Pile Height (Nominal)	1 1/2	inches	D-5823
Face Weight	50	oz/yd ²	D-5848
Total Fabric Weight	78	oz/yd ²	D-5848
Primary Backing Weight	6	oz/yd ²	D-5848
Secondary Coating Weight	22	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	> 400	in/hr	D-1551
Fabric Width	15	ft	-