



PET PREMIUM

With double the drainage, this easy-to-clean grass keeps pets safe and happy. Ideal for pet play and agility, including animals of all sizes, this is the perfect pet grass for both residential and commercial applications.



SUPER YARN™ TECHNOLOGY

SANITIZED®
ANTIMICROBIAL


DUALCHILL™
IR REFLECTIVE

STATBLOCK™
ANTI-STATIC

SKU	ST343_PETS
Grass Zone Yarn/Color	PE / Field Green / Apple
Grass Zone Denier	10,800 / 6
Thatch Zone Yarn/Color	PE / Field Green / Beige
Thatch Zone Denier	5,000 / 8
Grass Zone Yarn Shape	Omega
Finished Pile Height	1 1/2"
Finished Pile Weight	80 oz.
Backing	13PP/18PET 2pt / 22oz. EnviroLoc+™
Tuft Gauge	3/8"
Total Weight	108 oz.
Tuft Bind	> 8 lbs.
Permeability	> 1,000 inches p/hr
Features	Sanitized®, EnviroLoc+™, StatBlock™ Anti-Static, DualChill™ IR Reflective, SuperDrain+™, Deluster, UV Stabilizers
Test Data	ASTM E108 CLASS A FIRE, D2859, EN71, F1292, F1951, RCRA 8 TCLP, CAL 1350

- LIMITED LIFETIME WARRANTY*
- 2X THE DRAINAGE CAPABILITIES
- USE IN ALL CLIMATES AND REGIONS
- FOR MOST PET SIZES AND BREEDS

ASK ABOUT OUR...
USDA CERTIFIED ORGANIC INFILL SYSTEM



USDA CERTIFIED BIOBASED PRODUCT
PRODUCT 64%

SYNTipede X43 is a USDA Certified Bio-Based artificial grass system in combination with organic infill, able to display a unique USDA label highlighting its percentage of biobased content.



PETS





Primary Yarn Polymer	Polyethylene	Primary Backing	13PP/18PET 2pt
Yarn Cross Section	Omega	Coating Type	22 oz. EnviroLoc+
Standard Color	Field Green / Apple	PE Yarn Denier / Ends	10,800 / 6
Fabric Construction	Tufted	Texturized Thatch Denier / Ends	5,000 / 8
Second Yarn Polymer Thatch	Polyethylene	Warranty Period	Limited Lifetime
Secondary Yarn Color	Field Green / Beige		

FINISH FABRIC	ENGLISH SYSTEM		ASTM TEST
	Nominal Specification	Value	Units
Pile Height (Nominal)	1 1/2	inches	D-5823
Face Weight	80	oz/yd ²	D-5848
Total Fabric Weight	108	oz/yd ²	D-5848
Primary Backing Weight	6	oz/yd ²	D-5848
Secondary Coating Weight	22	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	> 1,000	in/hr	D-1551
Fabric Width	15	ft	-

