



SYNLAWN®

Plant-Based Artificial Grass

PRODUCT SPECIFICATIONS



ROOFDECK PREMIUM

With an **ASTM E-108 CLASS A FIRE RATING**, this is the ideal turf for even the most demanding ROOF applications. Featuring the safety and benefits of Super Yarn™ Technology, this grass style will beautify any space while beating the strictest safety codes.

SKU	SAX47_ROOF
Grass Zone Yarn/Color	PE / Field Green / Olive / Apple
Grass Zone Denier	9,900 / 9
Thatch Zone Yarn/Color	PE / Field Green / Beige
Thatch Zone Denier	5,000 / 8
Grass Zone Yarn Shape	Soft Omega
Finished Pile Height	1 5/8"
Finished Pile Weight	100 oz.
Backing	13PP/18PET 2pt / 22oz. EnviroLoc+™
Tuft Gauge	3/8"
Total Weight	128 oz.
Tuft Bind	> 8 lbs.
Permeability	> 1,000 inches p/hr
Features	Sanitized®, EnviroLoc+™, StatBlock™ Anti-Static, DualChill™ IR Reflective, SuperDrain+™, Deluster, UV Stabilizers
Test Data	ASTM E108 CLASS A FIRE, C518, D2859, EN71, F2765, F355a, F1292, F1551, F1951, RCRA 8 TCLP, CAL 1350



SUPER YARN™ TECHNOLOGY

SANITIZED®
ANTIMICROBIAL

DUALCHILL™
IR REFLECTIVE

STATBLOCK™
ANTI-STATIC



ASTM E108 CLASS A FIRE RATING



LIMITED LIFETIME WARRANTY*




USE IN ALL CLIMATES AND REGIONS



SAFE FOR COMMERCIAL USE

ASK ABOUT OUR...

**USDA CERTIFIED
ORGANIC INFILL
SYSTEM**



**USDA
CERTIFIED
BIOBASED
PRODUCT**
PRODUCT 67%

SYNAugustine 347 is a USDA Certified Bio-Based artificial grass system in combination with organic infill, able to display a unique USDA label highlighting its percentage of biobased content.



ROOF



SYNLAWN®
a sportgroup company

SYNLAWN.COM • SYNLAWNGOLF.COM • (866) 796-5296



MADE IN

U. S. A.



SPECIFICATIONS SUBJECT TO CHANGE

03.17.2024

Primary Yarn Polymer	Polyethylene	Primary Backing	13PP/18PET 2pt
Yarn Cross Section	Soft Omega	Coating Type	22 oz. EnviroLoc+
Standard Color	Field Green / Olive / Apple	PE Yarn Denier / Ends	9,900 / 9
Fabric Construction	Tufted	Texturized Thatch Denier / Ends	5,000 / 8
Second Yarn Polymer Thatch	Polyethylene	Warranty Period	Limited Lifetime
Secondary Yarn Color	Field Green / Beige		

FINISH FABRIC	ENGLISH SYSTEM		ASTM TEST
	Nominal Specification	Value	Units
Pile Height (Nominal)	1 5/8	inches	D-5823
Face Weight	100	oz/yd ²	D-5848
Total Fabric Weight	128	oz/yd ²	D-5848
Primary Backing Weight	6	oz/yd ²	D-5848
Secondary Coating Weight	22	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	14,900	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	> 1,000	in/hr	D-1551
Fabric Width	15	ft	-