



SYNTIPEDE X43

Extreme durability with soft fibers ideal for residential and commercial applications make this an ideal selection for high foot traffic applications, including school playgrounds, public parks, and multiple commercial uses.

SKU	STX43
Grass Zone Yarn/Color	PE / Field Green / Apple
Grass Zone Denier	10,800 / 6
Thatch Zone Yarn/Color	PE / Field Green / Beige
Thatch Zone Denier	5,000 / 8
Grass Zone Yarn Shape	Omega
Finished Pile Height	1 1/2"
Finished Pile Weight	100 oz.
Backing	13PP/18PET 2pt / 22oz. EnviroLoc+™
Tuft Gauge	3/8"
Total Weight	128 oz.
Tuft Bind	> 8 lbs.
Permeability	> 1,000 inches p/hr
Features	Sanitized®, EnviroLoc+™, StatBlock™ Anti-Static, DualChill™ IR Reflective, SuperDrain+™, Deluster, UV Stabilizers
Test Data	USDA SYSTEM, ASTM E108 CLASS A FIRE, D2859, C518, EN71, F1292, RCRA 8 TCLP, CAL 1350, IPEMA



SUPER YARN™ TECHNOLOGY

SANITIZED®
ANTIMICROBIAL

DUALCHILL™
IR REFLECTIVE

STATBLOCK™
ANTI-STATIC



LIMITED LIFETIME WARRANTY*



OPTIMAL DRAINAGE > 1,000" P/HR




USE IN ALL CLIMATES AND REGIONS



IDEAL FOR HIGH FOOT-TRAFFIC AREAS

ASK ABOUT OUR... USDA CERTIFIED ORGANIC INFILL SYSTEM



**USDA
CERTIFIED
BIOBASED
PRODUCT**
PRODUCT 64%

SYNTIpeDE X43 is a USDA Certified Bio-Based artificial grass system in combination with organic infill, able to display a unique USDA label highlighting its percentage of biobased content.



**SYNLAWN**[®]The **Greenest** Turf on Earth[™]**SYNTIPEDE X43**

Primary Yarn Polymer	Polyethylene	Primary Backing	13PP/18PET 2pt
Yarn Cross Section	Omega	Coating Type	22 oz. EnviroLoc+
Standard Color	Field Green / Apple	PE Yarn Denier / Ends	10,800 / 6
Fabric Construction	Tufted	Texturized Thatch Denier / Ends	5,000 / 8
Second Yarn Polymer Thatch	Polyethylene	Warranty Period	Limited Lifetime
Secondary Yarn Color	Field Green / Beige		

FINISH FABRIC	ENGLISH SYSTEM		ASTM TEST
	<i>Nominal Specification</i>	<i>Value</i>	<i>Units</i>
Pile Height (Nominal)	1 1/2	inches	D-5823
Face Weight	100	oz/yd ²	D-5848
Total Fabric Weight	128	oz/yd ²	D-5848
Primary Backing Weight	6	oz/yd ²	D-5848
Secondary Coating Weight	22	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	> 1,000	in/hr	D-1551
Fabric Width	15	ft	-

**SYNLAWN**[®]
a sportgroup company

SYNLAWN.COM • SYNLAWNGOLF.COM • (866) 796-5296

THEGREENESTTURFONEARTH.COM

**MasterSpec**[®]

CADETAILLS.COM

SPECIFICATIONS SUBJECT TO CHANGE

03.17.2024