



SYNSPORT (COLORS)

Featuring bold colors and soft, low-friction turf blades, this turf is ideal for multi-use activity zones, wayfinding, lines, golf bunkers, and hazards.



5 COLORS IN-STOCK

WHITE | YELLOW | VEGAS GOLD | FLORIDA BLUE | BLACK
ASK ABOUT CUSTOM COLORS

SKU	SYNSP (COLORS)
Grass Zone Yarn/Color	PE / 5 Colors Available
Grass Zone Denier	10,800 / 6
Thatch Zone Yarn/Color	PE / FL Blue = Black Thatch
Thatch Zone Yarn/Color	PE / All Other = Matches Turf Color
Thatch Zone Denier	5,400 / 8
Grass Zone Yarn Shape	Legend Mono
Finished Pile Height	1"
Finished Pile / Total Weight	58 oz. / 86 oz.
Backing	13PP/18PET 2pt / 22oz. EnviroLoc+™
Tuft Gauge	3/8"
Tuft Bind	> 8 lbs.
Permeability	> 1,000 inches p/hr
Features	UV Stabilizers, Deluster

POWERED BY



ACTIVITY & MOTION



ENVIROLOC+™
PLANT-BASED



HEATBLOCK
TECHNOLOGY



LANDSCAPE



PETS



PLAY



MULTI-USE



GOLF





SYNSPORT (COLORS)



Official Synthetic Surface

FINISH FABRIC	ENGLISH SYSTEM		ASTM TEST
	Nominal Specification	Value	Units
Pile Height (Nominal)	1	inches	D-5823
Face Weight	58	oz/yd ²	D-5848
Total Fabric Weight	86	oz/yd ²	D-5848
Primary Backing Weight	6	oz/yd ²	D-5848
Secondary Coating Weight	22	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,300	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	> 1,000	in/hr	EN-12616
Fabric Width	15	ft	-

TESTING DATA

FIRE	ASTM D2859, ASTM E648
HEAVY METALS	EN-71
EMISSIONS	CAL1350
DRAINAGE	EN 12616
OTHER	ASTM F1292, ASTM F1951



SYNLAWN.COM • SYNLAWNGOLF.COM

THEGREENESTTURFONEARTH.COM

MasterSpec®



CADETAILS.COM

SPECIFICATIONS SUBJECT TO CHANGE

01.07.2026