



SKU	SS301		ne pros, it off every level.
Grass Zone Yarn/Color	Nylon / Verde		5
Grass Zone Denier	7,000 / 8	0	LIMITED LIFET
Thatch Zone Yarn/Color			NYLON FIBERS
Thatch Zone Denier			
Grass Zone Yarn Shape	Textured Diamond		HOLDS GOLF T
Finished Pile Height	1″	Ø	IDEAL FOR DRI
Finished Pile / Total Weight	120 oz. / 146 oz.		
Backing	13PP/18PET 2pt / 20 oz Black PU	INSTALLATION E	DETAILS AVAILABLE AT
Tuft Gauge	3/16"		ADdetails
Tuft Bind	> 8 lbs.		ERSPEC [®]
Permeability	-	CONTACT YOUR	LOCAL SYNLAWN FOR
Features	UV Stabilizers, HeatBlock		
Test Data	CAL 1350, ASTM D2859		

TEE STRIKE

The ultimate turf for golf tee lines, tee boxes, and hitting mats, trusted by professionals for its superior performance. With a dense 1" nylon pile, it holds standard golf tees, reduces club head drag, and ensures smooth, natural swings. Tee Strike delivers exceptional durability, accuracy, and consistency, making it the premier choice for both practice and club-fitting setups. Built for the pros, it offers reliable performance for players at every level.







U. S. A.

Official Synthetic Surface



Official Synthetic Surface



Primary Yarn Polymer	Nylon		
Yarn Cross Section	Textured Diamond	Primary Backing	13PP/18PET 2pt
Standard Color	Verde	Coating Type	20 oz Black PU
Fabric Construction	Tufted	PE Yarn Denier / Ends	7,000 / 8
Second Yarn Polymer Thatch		Texturized Thatch Denier / Ends	-
Secondary Yarn Color	· .	Warranty Period	Limited Lifetime

FINISH FABRIC	ENGLISH	SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1	inches	D-5823
Face Weight	120	oz/yd²	D-5848
Total Fabric Weight	146	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	20	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	7,000	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Guage	3/16	inches	D-5793
Flammability	Passed		D-2859
Water Permeability			-
Fabric Width	6 & 12	ft	-



THEGREENESTTURFONEARTH.COM

MasterSpec°



SPECIFICATIONS SUBJECT TO CHANGE

02.10.2025