

SKU	SYN48 (+PAD)	
Grass Zone Yarn	Polyethylene	
Grass Zone Denier	5,400 / 8	
Thatch Zone Yarn/Color	-	
Thatch Zone Denier	-	
Grass Zone Yarn Shape	Textured Diamond	
Finished Pile Height	3/4"	
Finished Pile / Total Weight	48 oz. / 120 oz.	
Backing	13PP/18PET 2pt / 5mm Cushion	
Tuft Gauge	3/16"	
Tuft Bind	> 8 lbs.	
Permeability	-	
Features	Deluster, UV Stabilizers	
Test Data	ASTM D2859, ASTM E648, ASTM F1951	

SYNPLAY 48 (+PAD)

This vibrant, colorful turf with a low-pile, low-friction surface is perfect for indoor activity and agility zones. Designed for durability and easy maintenance, it provides a consistent, high-performance surface for a variety of applications.



7 COLORS IN-STOCK

BLACK | FL BLUE | GREEN | GREY | RED | RED CLAY | WHITE ASK ABOUT CUSTOM COLORS & DESIGNS





SAFE, SOFT, DURABLE SURFACE

FOR DAYCARE, GYMS AND TRAINING FACILITIES



















SYNPLAY 48 (+PAD)



Official Synthetic Surface

Polyethylene		
Textured Diamond	Primary Backing	13PP/18PET 2pt
7 Colors In Stock	Cushion	5mm
Tufted	PE Yarn Denier / Ends	5,400 / 8
	Texturized Thatch Denier / Ends	-
	Warranty Period	Limited Lifetime
	Textured Diamond 7 Colors In Stock Tufted	Textured Diamond Primary Backing 7 Colors In Stock Cushion Tufted PE Yarn Denier / Ends Texturized Thatch Denier / Ends

FINISH FABRIC	ENGLISH	SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	3/4	inches	D-5823
Face Weight	48	oz/yd²	D-5848
Total Fabric Weight	120	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Cushion Weight	60	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	5,400	Denier	D-1577
Elongation to Break	> 60	%	D-2256
Yarn Breaking Strength	> 19	lbs.	D-5793
Machine Gauge	3/16	inches	D-5793
Flammability	Passed		D-2859
Water Permeability			-
Fabric Width	15	ft	-



