



SYNPLAY 60 (NO PAD)

This colorful, low-pile height, low-friction turf is ideal for schools, daycare, gyms, training facilities, weight rooms and activity areas.



8 COLORS IN-STOCK

BLACK | FL BLUE | GREEN | GREY | NAVY | RED | WHITE | YELLOW
ASK ABOUT CUSTOM COLORS & DESIGNS

SKU	SPG60 (No Pad)
Grass Zone Yarn	Polyethylene
Grass Zone Denier	Green: 8,400 / 1 Colors: 10,000 / 1
Thatch Zone Yarn/Color	Green: Nylon / Turf Green Navy/Grey/Black: PE / Black All Others: PE / Matches Turf Color
Thatch Zone Denier	Green: 6,000 / 8 Colors: 5,400 / 8
Grass Zone Yarn Shape	Slit Film
Finished Pile Height	3/4"
Finished Pile / Total Weight	58 oz. / 77 oz.
Backing	13PP/18 PET 2-Part / 13 oz Black PU
Tuft Gauge	3/16"
Tuft Bind	> 8 lbs.
Permeability	>40 inches p/hr
Features	Deluster, UV Stabilizers

POWERED BY



ACTIVITY & MOTION



ENERGY ABSORBING



HEATBLOCK TECHNOLOGY





SYNPLAY 60 (NO PAD)



Official Synthetic Surface

FINISH FABRIC	ENGLISH SYSTEM		ASTM TEST
	Nominal Specification	Value	Units
Pile Height (Nominal)	3/4	inches	D-5823
Face Weight	58	oz/yd ²	D-5848
Total Fabric Weight	77	oz/yd ²	D-5848
Primary Backing Weight	6	oz/yd ²	D-5848
Secondary Coating Weight	13	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	14,400/15,400	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/16	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	>40	in/hr	F-1551

TESTING DATA

FIRE	ASTM D2859, ASTM E648
HEAVY METALS	EN-71
EMISSIONS	CAL1350
DRAINAGE	ASTM F1551
OTHER	ASTM F1292, ASTM F1951



THEGREENESTTURFONEARTH.COM



MasterSpec®

CADETAILLS.COM

SYNLAWN.COM • SYNLAWNGOLF.COM

SPECIFICATIONS SUBJECT TO CHANGE

12.10.2025