



## SYNTIPEDE X43

Soft fibers with extreme durability make this the perfect selection for any residential or commercial applications with high foot-traffic areas including school playgrounds, public parks, and multiple other uses.



### SUPER YARN™ TECHNOLOGY

**SANITIZED®**  
ANTIMICROBIAL

**DUALCHILL™**  
IR REFLECTIVE

**STATBLOCK™**  
ANTI-STATIC

SKU	STX4B
Grass Zone Yarn/Color	PE / Field Green/Apple
Grass Zone Denier	10,800/6
Thatch Zone Yarn/Color	PE / Field Green/Beige
Thatch Zone Denier	5,000/8
Grass Zone Yarn Shape	Biomimetic™ C
Finished Pile Height	1 1/2"
Finished Pile / Total Weight	100 oz. /128 oz.
Backing	13PP/18PET 2pt / 22oz. EnviroLoc+™
Tuft Gauge	3/8"
Tuft Bind	> 8 lbs.
Permeability	> 1,000 inches p/hr
Features	Sanitized®, EnviroLoc+™, StatBlock™ Anti-Static, DualChill™ IR Reflective, Deluster, UV Stabilizers, Biomimetic™
Test Data	EN 12616, CAL1350, ASTM C518, ASTM D7138, ASTM E108, ASTM F1292, ASTM F1951, ASTM F2765, EN-71, RCRA 8 TCLP



LIMITED LIFETIME WARRANTY



OPTIMAL DRAINAGE > 1,000" P/HR




USE IN ALL CLIMATES AND REGIONS



IDEAL FOR HIGH FOOT-TRAFFIC AREAS

ASK ABOUT OUR...  
**USDA CERTIFIED ORGANIC INFILL SYSTEM**



**USDA CERTIFIED BIOBASED PRODUCT**  
PRODUCT 64%

SYNTIPEDE X43 is a USDA Certified Bio-Based artificial grass system in combination with organic infill, able to display a unique USDA label highlighting its percentage of biobased content.





# SYNTIPEDE X43



Official Synthetic Surface

Primary Yarn Polymer	Polyethylene	Primary Backing	13PP/18PET 2pt
Yarn Cross Section	Biomimetic™ C	Coating Type	22 oz. EnviroLoc+
Standard Color	Field Green/Apple	PE Yarn Denier / Ends	10,800/6
Fabric Construction	Tufted	Texturized Thatch Denier / Ends	5,000/8
Second Yarn Polymer Thatch	Polyethylene	Warranty Period	Limited Lifetime
Secondary Yarn Color	Field Green/Beige		

FINISH FABRIC	ENGLISH SYSTEM		ASTM TEST
	Nominal Specification	Value	Units
Pile Height (Nominal)	1 1/2	inches	D-5823
Face Weight	100	oz/yd <sup>2</sup>	D-5848
Total Fabric Weight	128	oz/yd <sup>2</sup>	D-5848
Primary Backing Weight	6	oz/yd <sup>2</sup>	D-5848
Secondary Coating Weight	22	oz/yd <sup>2</sup>	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	> 1,000	in/hr	EN 12616
Fabric Width	15	ft	-



THEGREENESTTURFONEARTH.COM



MasterSpec®

CADETAILS.COM

SYNLAWN.COM • SYNLAWNGOLF.COM

SPECIFICATIONS SUBJECT TO CHANGE

01.19.2025