

PRODUCT SPECIFICATIONS



С	v	н	
S	Ν	U	

Grass Zone Yarn/Color

Grass Zone Denier

Thatch Zone Yarn/Color

Thatch Zone Denier

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile / Total Weight

Backing

Tuft Gauge

Tuft Bind

Permeability

Features

Test Data

PTPLT

Nylon+PE / Field Green/Olive/Apple

10,800/6

PE / Field Green / Beige

5,000/8

Legend Mono

1 1/2"

100 oz. / 128 oz.

13PP/18PET 2pt / 22oz. EnviroLoc+™

3/8"

> 8 lbs.

> 1,000 inches p/hr

Sanitized*, EnviroLoc+™, StatBlock™ Anti-Static, DualChill™ IR Reflective, Deluster, UV Stabilizers

EN 12616, CAL1350, ASTM C518, ASTM D7138, ASTM E108, ASTM F1292, ASTM F1951, ASTM F2765, EN-71, RCRA 8 TCLP

PET PLATINUM

Offering superior drainage and unmatched durability, Pet Platinum stands out as the top choice for high-traffic pet areas like residential yards, commercial pet facilities, and agility spaces. Designed for reliability and resilience it provides a clean, safe, and comfortable surface for a wide range of pet applications where performance truly matters.



SUPER YARN™ TECHNOLOGY

SANITIZED® ANTIMICROBIAL

DUALCHILL™ IR REFLECTIVE

STATBLOCK™ ANTI-STATIC



LIMITED LIFETIME WARRANTY



2X THE DRAINAGE CAPABILITIES



USE IN ALL CLIMATES AND REGIONS



IDEAL FOR HEAVY USE PET AREAS

ASK ABOUT OUR... USDA CERTIFIED ORGANIC INFILL SYSTEM



Pet Platinum is a USDA Certified Bio-Based artificial grass system in combination with organic infill, able to display a unique USDA label highlighting its percentage of biobased content.

















PET PLATINUM



Official Synthetic Surface

Primary Yarn Polymer	Polyethylene	
Yarn Cross Section	Legend Mono	
Standard Color	Field Green/Olive/Apple	
Fabric Construction	Tufted	
Second Yarn Polymer Thatch	Polyethylene	
Secondary Yarn Color	Field Green/Beige	

Primary Backing	13PP/18PET 2pt	
Coating Type	22 oz. EnviroLoc+	
PE Yarn Denier / Ends	10,800/6	
Texturized Thatch Denier / Ends	5,000/8	
Warranty Period	Limited Lifetime	

FINISH FABRIC	ENGLISH	SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 1/2	inches	D-5823
Face Weight	100	oz/yd²	D-5848
Total Fabric Weight	128	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	> 1,000	in/hr	EN 12616
Fabric Width	15	ft	-





