





Grass Zone Yarn/Color

Grass Zone Denier

SKU

Thatch Zone Yarn/Color

Thatch Zone Denier

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile / Total Weight

Backing

Tuft Gauge

Tuft Bind

Permeability

Features

Test Data

PTPRT

Nylon+PE / Field Green/Olive/Apple

10,800/6

PE / Field Green/Beige

5,000/8

Legend Mono

1 1/2"

80 oz. / 108 oz.

13PP/18PET 2pt / 22oz. EnviroLoc+™

3/8"

> 8 lbs.

> 1,000 inches p/hr

Sanitized®, EnviroLoc+™, StatBlock™ Anti-Static, DualChill™ IR Reflective, Deluster, UV Stabilizers

EN 12616, CAL1350, ASTM D2859, ASTM D7138, ASTM E108, ASTM F1292, ASTM F1951, ASTM F2765, EN-71, RCRA 8 TCLP, BS EN 13746

PET PREMIUM

Designed with pets in mind, Pet Premium features double the drainage capacity for superior cleanliness and comfort. Perfect for pet play and agility, this turf is safe for animals of all sizes and well-suited for both residential and commercial applications. .



SUPER YARN™ TECHNOLOGY

SANITIZED® ANTIMICROBIAL

DUALCHILL™ IR REFLECTIVE ANTI-STATIC



LIMITED LIFETIME WARRANTY



2X THE DRAINAGE CAPABILITIES



USE IN ALL CLIMATES AND REGIONS



FOR MOST PET SIZES AND BREEDS

ASK ABOUT OUR... **USDA CERTIFIED**



Pet Premium is a USDA Certified Bio-Based artificial grass system in combination with organic infill, able to display a unique USDA label highlighting its percentage of biobased

















PET PREMIUM



Official Synthetic Surface

Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	Legend Mono	Primary Backing	13PP/18PET 2pt
Standard Color	Field Green/Olive/Apple	Coating Type	22 oz. EnviroLoc+
Fabric Construction	Tufted	PE Yarn Denier / Ends	10,800/6
Second Yarn Polymer Thatch	Polyethylene	Texturized Thatch Denier / Ends	5,000/8
Secondary Yarn Color	Field Green/Beige	Warranty Period	Limited Lifetime

FINISH FABRIC	ENGLISH	SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 1/2	inches	D-5823
Face Weight	80	oz/yd²	D-5848
Total Fabric Weight	108	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	> 1,000	in/hr	EN 12616
Fabric Width	15	ft	-

