





_	17	ı	
5	Κ	U	J
_	٠.	•	•

Grass Zone Yarn/Color

**Grass Zone Denier** 

Thatch Zone Yarn/Color

Thatch Zone Denier

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile / Total

Weight

Backing

**Tuft Gauge** 

**Tuft Bind** 

Permeability

**Features** 

**Test Data** 

S321T

Nylon + PE / Field Green/Olive/Apple

10,800/6

PE / Meadow Green

5,600/8

Legend Mono

1 1/2"

80 oz. / 108 oz.

13PP/18PET 2pt / 22oz. EnviroLoc+™

3/8"

> 8 lbs.

> 1,000 inches p/hr

Sanitized\*, EnviroLoc+™, StatBlock™ Anti-Static, DualChill™ IR Reflective, Deluster, UV Stabilizers

CAL1350, ASTM D2859, ASTM D7138, ASTM F1292, ASTM F2765, RCRA 8 TCLP, BS EN 13746

## **SYNTIPEDE 321**

With superior durability this grass variety delivers high performance and beauty. Featuring Super Yarn™ technology, this product creates a durable surface perfect for active children and pets, giving you peace of mind for all types of landscaping projects.



## **SUPER YARN™ TECHNOLOGY**

**SANITIZED**® ANTIMICROBIAL

**DUALCHILL™** IR REFLECTIVE

STATBLOCK™ ANTI-STATIC



LIMITED LIFETIME WARRANTY



OPTIMAL DRAINAGE > 1,000" P/HR



**USE IN ALL CLIMATES AND REGIONS** 



IDEAL FOR HIGH FOOT-TRAFFIC AREAS

ASK ABOUT OUR...
USDA CERTIFIED
ORGANIC INFILL
SYSTEM



SYNTipede 321 is a USDA Certified Bio-Based artificial grass system in combination with organic infill, able to display a unique USDA label highlighting its percentage of biobased content.























## **SYNTIPEDE 321**



## Official Synthetic Surface

Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	Legend Mono	Primary Backing	13PP/18PET 2pt
Standard Color	Field Green/Olive/Apple	Coating Type	22 oz. EnviroLoc+
Fabric Construction	Tufted	PE Yarn Denier / Ends	10,800/6
Second Yarn Polymer Thatch	Polyethylene	Texturized Thatch Denier / Ends	5,600/8
Secondary Yarn Color	Meadow Green	Warranty Period	Limited Lifetime

FINISH FABRIC	ENGLISH	SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 1/2	inches	D-5823
Face Weight	80	oz/yd²	D-5848
Total Fabric Weight	108	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	16,400	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Guage	3/8	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	> 1,000	in/hr	D-1551
Fabric Width	15	ft	-



